

BRUMMER SUPER 65

CONTACT ADHESIVE

PRODUCT DATA

TECHNICAL INFORMATION

BRUMMER SUPER 65 is a one component Polychloroprene contact cement, yellowish in colour, with a medium brushable consistency.

The ideal storing temperature is approx. 15°C (59°F)

Viscosity	35
Mass per Litre (25°C)	.850 Kg
Flash Point	Minus 20°C – Highly flammable
Solids Content	20%
Storage	1 Year – well sealed containers
Solvent Cleaner	Neoprene Solvent

HEALTH & SAFETY

Not to be exposed near a naked flame.

Use protective clothing.

Not to be used in a confined area without adequate ventilation.

PACKAGING

CODE	SIZE	PACKING
4102Z	125 ml	Box 80
4102B	250 ml	Box 45
4102C	500ml	Box 18
4102D	1 Lt	Box 10
4102F	5 Lt	Box 2/Tray 4
4102G	25 Lt	Each
4102A	200 Lt	Each

Note For a Material Safety Data sheet and technical data refer to website.

DISCLAIMER

Seller makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose, except that the product does not infringe any valid patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall the seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise. Onus is on the customer to ensure that the product purchased is suitable for the purpose intended and to test apply all products prior to bulk application.

CONTACT

Manufactured by: BRUMMER ADHESIVES SA (Pty) Ltd
21 Assegaai Road PAROW INDUSTRIAL 7490
P O Box 6043 PAROW EAST 7501

Tel: 021 931 2131
Fax: 021 932 3998 e-mail: sales@brummersa.co.za